

CHAMBER FURNACES

standard equipment

The furnace comes with:

- An electrical cabinet integrated in the frame
- Ceramic thermocouple (K,S,B) according to temperature



options

- LiteCell® insulation without RCF classification
- Temperature recording
- Programmable trap and ventilation exhaust
- Sealed refractory steel muffle

technical characteristics

Temperature (°C)	Volume (L)	Reference	Internal dimensions (mm)			External dimensions (mm)			Power (kW)	Supply (V)
			H	L	P	H	L	P		
1100°C	5	FC1105	150	150	250	530	550	450	3	230
	10	FC1110	200	200	300	630	650	550	4	230
	50	FC1150	350	350	400	780	800	650	9	400x3
1500°C	5	FC1505	150	150	250	530	550	450	3	230
	10	FC1510	200	200	300	630	650	550	4	230
	50	FC1550	350	350	400	780	800	650	9	400x3
1700°C	5	FC1705	150	150	300	650	900	610	4	230
	10	FC1710	230	230	250	700	1000	610	6	230
	50	FC1750	350	350	400	1700	905	905	18	400x3
1800°C	5	FC1805	150	150	300	650	900	610	4	230
	10	FC1810	230	230	250	700	1000	610	6	230
	50	FC1850	350	350	400	1700	905	905	18	400x3

Other dimensions available on request

Specifications and photos are not contractual, subjected to technical changes